

# HydroMaxx® HDPE NON-Split Tubing Spec Sheet

## Features:

- HDPE offers greater rigidity and durability than LDPE and may be direct buried
- Available in sizes from 1/2 inch to 2 inch in Black, Orange and Yellow colors.
- Constructed from HDPE, High density polyethylene, solvent and acid resistant.
- Polyethylene exterior is designed to absorb light to medium impact levels
- Prevents delicate cables and fibers from crush, cut and wear damage and deterioration.
- Abrasion, solvent and acid resistant
- Flame Retardant
- Working Temperatures: -40° F to +200° F.
- Made in North America

## Applications: (Coverage Protection for)

- Fiber optic cables
- Ethernet cables
- Home theater cables
- Power cables
- Speaker wiring

## Availability:

- Diameters: 1/2", 3/4", 1", 1.5", 2"
- Colors: Black, Orange, Yellow
- Lengths: 100 ft



Size inches	ID "A"		OD "B"		Wall "C"	Corrugated HT. "E"
	Min	Max	Min	Max	Min	Reference
1/2"	0.473	0.516	0.664	0.700	0.005	0.094
3/4"	0.707	0.759	0.950	0.989	0.005	0.118
1"	1.020	1.069	1.251	1.304	0.006	0.117
1 1/2"	1.566	1.647	1.867	1.947	0.006	0.15
2"	1.969	2.038	2.285	2.388	0.011	0.167

