

HydroMaxx® Non Metallic Liquid Tight Conduit Spec Sheet



Features:

- UL Rated Liquid Tight Non-Metallic Conduit
- Flexible - Can be used in extremely Tight Quarters
- Light Weight - Lower Installed Costs
- Resists Corrosion, Oil and Water
- Resists Crushing and Stretching, Smooth Inside for Easier Wire Pulling
- Sunlight Resistant with Quick Installation - Cuts with Utility Knife or PVC Cutter
- Integral Rigid and Flexible PVC Construction
- Operating Temperatures: 14 degrees F to 140 degrees F.

Applications:

- HVAC Equipment
- Machine Tools
- Marine Equipment
- Motors and Controls
- Printing Equipment
- Pumps
- Refrigeration Equipment
- Transformer Connections
- Outdoor Lighting



Availability:

- Diameters: 3/8", 1/2", 3/4", 1", 1.25", 1.5", 2"
- Colors: Gray
- Lengths: 25ft, 50ft, 100 ft

Liquid Tight Conduit Technical Specification Chart				
Size inches	Inside Diameter (inches)		Outside Diameter (inches)	
	Min	Max	Min	Max
3/8"	0.484	0.504	0.690	0.710
1/2"	0.622	0.642	0.820	0.840
3/4"	0.820	0.840	1.030	1.050
1"	1.041	1.066	1.290	1.315
1 1/4"	1.380	1.410	1.630	1.660
1 1/2"	1.575	1.600	1.865	1.900
2"	2.020	2.045	2.340	2.375