

# HydroMaxx® Opaque Colored Vinyl Tubing Spec Sheet

## Features:

- **Super Smooth** - Made from virgin PVC, our vinyl tubing is blemish free. and can be used for anything from retail products to industrial uses. There are no markings or printing on our vinyl tubing, ever.
- **Resistant to Chemicals** - It is suitable for liquids, chemicals and gases and more. It is non-marking, non-conductive and silicone free.
- **Smooth Inside and Outside** - Allows Unrestricted Flow - Shore A Hardness allows maximum flexibility but won't allow the tubing to collapse or crimp.
- **Non-Toxic PVC Tubing** Can be Steam Sterilized, Manufactured to FDA and USDA Standards. All of our vinyl tubing is BPA and phalate free.
- PVC is resistant to abrasions and corrosion. Our PVC material is designed to reduce against hardening and discoloration. Built to last.
- **Working temperatures:** 5 degrees F to 150 degrees F
- Easily conforms to barbed vinyl tubing fittings and connectors and is clamped using hose, wire or ratcheting clamps.

## Applications:

- Use for Refrigeration and Air Conditioning condensation drains
- Ideal for applications in Laboratories, chemical and Industrial Plants
- Use for aquariums, drain hoses, bath and spa jets, dishwasher inlets and more
- Use for water softener and humidifier drains

## Availability:

- **Diameters:** 1/4", 3/8", 1/2", 3/4", 1"
- **Colors:** Red and Blue
- **Lengths:** 100 ft

**Vinyl Tubing Specification Chart**

Diameter		Wall Thickness	Working Pressure PSI
ID	OD		
1/4"	3/8"	1/16"	55
3/8"	1/2"	1/16"	45
1/2"	5/8"	1/16"	30
1/2"	3/4"	1/8"	45
5/8"	3/4"	1/16"	30
3/4"	1"	1/8"	35
1"	1 1/4"	1/8"	28