

HydroMaxx® Flexible Non-Toxic Vinyl Tubing Spec Sheet

Features:

- **Super Smooth** - Made from virgin PVC, our vinyl tubing is blemish free. There are no markings or printing on our vinyl tubing, ever.
- **Resistant to Chemicals** - It is suitable for liquids, chemicals and gases and more. It is non-marking, non-conductive and silicone free.
- **Smooth Inside and Outside** - Allows Unrestricted Flow - Shore A Hardness allows maximum flexibility but won't allow the tubing to collapse or crimp.
- **Non-Toxic PVC Tubing Can be Steam Sterilized**, Manufactured to FDA and USDA Standards. All of our vinyl tubing is BPA and phalate free.
- PVC is resistant to abrasions and corrosion. Our PVC material is designed to reduce against hardening and discoloration. Built to last.
- **Working temperatures: 5 degrees F to 150 degrees F**
- Easily conforms to barbed vinyl tubing fittings and connectors and is clamped using hose, wire or ratcheting clamps.

Applications:

- Use for Refrigeration and Air Conditioning condensation drains
- Ideal for applications in Laboratories, chemical and Industrial Plants
- **BLACK** - Water Garden, Koi Pond, Statuary and Fountain installations
- **CLEAR** - Use for aquariums, drain hoses, bath and spa jets, dishwasher inlets and more
- Use for water softener and humidifier drains

Availability:

- **Diameters:** 1/8", 1/4", 3/8", 1/2", 5/8", 3/4", 1"
- **Colors:** Black and Clear
- **Lengths:** 50', 100'



Vinyl Tubing Specification Chart

Diameter		Wall Thickness	Working Pressure PSI
ID	OD		
1/4"	3/8"	1/16"	55
3/8"	1/2"	1/16"	45
1/2"	5/8"	1/16"	30
1/2"	3/4"	1/8"	45
5/8"	3/4"	1/16"	30
3/4"	1"	1/8"	35
1"	1 1/4"	1/8"	28